




PRODUCT DETAILS



Dimensions



LLP-PRO-ST II MN122

(L01) LED 14250lm/740

1x122W, LED DRIVER, RAL 9006

Description

MOUNTING	Pole top / side entry installation (PMT)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Lenses (LNS)
LIGHT DISTRIBUTION	Direct
WIRING	External lead-in flexible cable Electronic control gear FIX / DALI / STEP DIM / INT DIM + CONSTANT LUMEN OUTPUT (ECC / EDO / EBC / EPO)

MATERIALS	Cover: PC Frame: sheet steel Housing: die-cast aluminium Tiltable spigot: die cast aluminium
SURFACE FINISH	Housing: grey RAL 9006 (G06)

VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	14250 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	122 W
SYSTEM EFFICACY	117 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>70 Ra
COLOUR TOLERANCE	5 SCDM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	60,000 hours / L80
AMBIENT OPERATING TEMPERATURE	From -40 °C to +50 °C
IP PROTECTION DEGREE	IP67
MECHANICAL IMPACT RESISTANCE	IK10
WINDAGE AREA SIDE / TOP	0,028 / 0,193 m ²
RECOMENDED MOUNTING HEIGHT	8-12 m
REPLACEMENT OF STANDARD	HPS 150 W
DIMENSIONS (L x W x H)	623 x 348 x 60 mm

WEIGHT	9,5 kg
---------------	--------