




PRODUCT DETAILS



Dimensions



LLP-PRO-ST II MN35

(L01) LED 3950lm/740 1x35W,
LED DRIVER, RAL 9006

Description

MOUNTING	Pole top / side entry installation (PMT)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Lenses (LNS)
LIGHT DISTRIBUTION	Direct
WIRING	External lead-in flexible cable Electronic control gear FIX / DALI / STEP DIM / INT DIM + CONSTANT LUMEN OUTPUT (ECC / EDO / EBC / EPO)
MATERIALS	Cover: PC Frame: sheet steel Housing: die-cast aluminium Tiltable spigot: die cast aluminium Housing: grey RAL 9006 (G06)
SURFACE FINISH	220-240 V, 50-60 Hz
VOLTAGE	> 0,95
POWER FACTOR	3950 lm
NET LUMEN OUTPUT (Ta=25°C)	+/- 10 %
LUMINOUS FLUX TOLERANCE	35 W
POWER CONSUMPTION	113 lm/W
SYSTEM EFFICACY	4000 K
CORRELATED COLOUR TEMPERATURE	>70 Ra
COLOUR RENDERING INDEX	5 SCDM
COLOUR TOLERANCE	A++ / A+ / A
EEC	II
PROTECTION CLASS	Passive
THERMAL MANAGEMENT	60,000 hours / L90
SERVICE LIFETIME (Ta=25°C)	From -40 °C to +50 °C
AMBIENT OPERATING TEMPERATURE	IP67
IP PROTECTION DEGREE	IK10
MECHANICAL IMPACT RESISTANCE	0,028 / 0,193 m ²
WINDAGE AREA SIDE / TOP	5-8 m
RECOMENDED MOUNTING HEIGHT	HPS 70 W
REPLACEMENT OF STANDARD	623 x 348 x 60 mm
DIMENSIONS (L x W x H)	

WEIGHT 9,4 kg