




PRODUCT DETAILS



Dimensions



LLP-PRO-ST II MN71

(L01) LED 8750lm/740 1x71W,
LED DRIVER, RAL 9006

Description

MOUNTING	Pole top / side entry installation (PMT)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Lenses (LNS)
LIGHT DISTRIBUTION	Direct
WIRING	External lead-in flexible cable Electronic control gear FIX / DALI / STEP DIM / INT DIM + CONSTANT LUMEN OUTPUT (ECC / EDO / EBC / EPO)
MATERIALS	Cover: PC Frame: sheet steel Housing: die-cast aluminium Tiltable spigot: die cast aluminium
SURFACE FINISH	Housing: grey RAL 9006 (G06)
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	8750 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	71 W
SYSTEM EFFICACY	123 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>70 Ra
COLOUR TOLERANCE	5 SCDM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	60,000 hours / L90
AMBIENT OPERATING TEMPERATURE	From -40 °C to +50 °C
IP PROTECTION DEGREE	IP67
MECHANICAL IMPACT RESISTANCE	IK10
WINDAGE AREA SIDE / TOP	0,028 / 0,193 m ²
RECOMENDED MOUNTING HEIGHT	7-10 m
REPLACEMENT OF STANDARD	HPS 100 W
DIMENSIONS (L x W x H)	623 x 348 x 60 mm

WEIGHT 9,4 kg