



PRODUCT DETAILS



Dimensions



LLP-PRO-ST-L173

(L01) LED 21400lm/740 1x173W,
LED DRIVER, RAL 9006

Description

MOUNTING	Pole top / side entry installation (PMT)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Lenses (LNS)
LIGHT DISTRIBUTION	Direct
WIRING	External lead-in flexible cable Electronic control gear FIX / DALI / STEP DIM / INT DIM + CONSTANT LUMEN OUTPUT (ECC / EDO / EBC / EPO)
MATERIALS	Cover: transparent hardened glass Frame: sheet steel Housing: die-cast aluminium Tiltable spigot: die cast aluminium Housing: grey RAL 9006 (G06)
SURFACE FINISH	
VOLTAGE	220-240 V, 50-60 Hz
POWER FACTOR	> 0,95
NET LUMEN OUTPUT (Ta=25°C)	21400 lm
LUMINOUS FLUX TOLERANCE	+/- 10 %
POWER CONSUMPTION	173 W
SYSTEM EFFICACY	124 lm/W
CORRELATED COLOUR TEMPERATURE	4000 K
COLOUR RENDERING INDEX	>70 Ra
COLOUR TOLERANCE	5 SDCM
EEC	A++ / A+ / A
PROTECTION CLASS	II
THERMAL MANAGEMENT	Passive
SERVICE LIFETIME (Ta=25°C)	Up to 100,000 hours / L80
AMBIENT OPERATING TEMPERATURE	From -35 °C to +40 °C
IP PROTECTION DEGREE	IP65
MECHANICAL IMPACT RESISTANCE	IK08
WINDAGE AREA SIDE / TOP	0,038 / 0,32 m ²
RECOMENDED MOUNTING HEIGHT	8-12 m
REPLACEMENT OF STANDARD	HPS 250 W
DIMENSIONS (L x W x H)	764 x 467 x 62 mm
WEIGHT	23 kg