



PRODUCT DETAILS



Dimensions



LLP-PRO-ST-L207

(L01) LED 24750lm/740 1x207W,
LED DRIVER, RAL 9006

Description

MOUNTING	Pole top / side entry installation (PMT)
LIGHT SOURCE	LED
OPTICAL SYSTEM	Lenses (LNS)
LIGHT DISTRIBUTION	Direct
WIRING	External lead-in flexible cable Electronic control gear FIX / DALI / STEP DIM / INT DIM + CONSTANT LUMEN OUTPUT (ECC / EDO / EBC / EPO)
MATERIALS	Cover: transparent hardened glass Frame: sheet steel Housing: die-cast aluminium Tiltable spigot: die cast aluminium Housing: grey RAL 9006 (G06)
SURFACE FINISH	220-240 V, 50-60 Hz
VOLTAGE	> 0,95
POWER FACTOR	24750 lm
NET LUMEN OUTPUT (Ta=25°C)	+/- 10 %
LUMINOUS FLUX TOLERANCE	207 W
POWER CONSUMPTION	120 lm/W
SYSTEM EFFICACY	4000 K
CORRELATED COLOUR TEMPERATURE	>70 Ra
COLOUR RENDERING INDEX	5 SDCM
COLOUR TOLERANCE	A++ / A+ / A
EEC	II
PROTECTION CLASS	Passive
THERMAL MANAGEMENT	Up to 100,000 hours / L80
SERVICE LIFETIME (Ta=25°C)	From -35 °C to +40 °C
AMBIENT OPERATING TEMPERATURE	IP65
IP PROTECTION DEGREE	IK08
MECHANICAL IMPACT RESISTANCE	0,038 / 0,32 m ²
WINDAGE AREA SIDE / TOP	10-15 m
RECOMENDED MOUNTING HEIGHT	REPLACEMENT OF STANDARD
REPLACEMENT OF STANDARD	HPS 400 W
DIMENSIONS (L x W x H)	764 x 467 x 62 mm
WEIGHT	23,6 kg